


OD1100

CRI 80 3000K 600 Lumens wall lamp



Multi-faceted fixture interior engineered to maximize LED module performance
LED module designed to deliver maximum light levels to work surface without fixture glare
Opaque white acrylic lens finish provides maximum optical comfort and effective light distribution.
The low profile dimmable unit is ETL damp listed and produces 600 lumens at 80+ Rnstruction or retrofit applications.

Performance

- Wall lamp is designed to provide 50,000 hours of life
- Energy-saving & Super bright, saving 75% energy compared with traditional troffer
- Decorative fashion

Construction

- Die-cast Aluminum for excellent heat dissipation
- IP54 Waterproof

Installation

- The products covered by this report are fixed luminaire for dry location use, . they are intended to be mounted on the outlet box
- Size:E=3.94"(100mm)*H=7.96"(202mm)



Specifications

Category	Wall Lamp	Individual Box Length (Inch)	9.85
Bulb Shape	N/A	Individual Box Width (Inch)	9.85
Bulb Base Type	N/A	Individual Box Height (Inch)	6.3
Bulb Base Finish	Integrated 'LED	Individual Box Weight Per Unit (Lbs)	2.46
Color Temperature	3000K	Carton Package Length (Inch)	26.77
Beam Angle	120°	Carton Package Width (Inch)	20.47
Finish	Marble Grey	Carton Package Height (Inch)	11.02
CRI	80	Carton Package Weight Per Unit (Lbs)	22.7
Average Life (Hours)	50000	Carton Quantity	8
Estimated Yearly Energy Cost (11 ¢/Kwh)	1.14	Lamp Type	LED
Life Based On 3Hrs/Day (Years)	45.66	Dry/Wet/Damp	Wet
Product Length (Inch)	N/A	Energy Star	NO
Product Width (Inch)	7.96	Power Factor	≥0.9
Product Height (Inch)	7.96	Current	79
Product Extension (Inch)	3.94	Lumen/Watt	65
Product Weight Per Unit (Lbs)	1.76	Warranty (Year)	5
Dimmable	NO	DLC (Yes/No)	No
Watts	10W	Input Voltage	120v
Watt Equivalent	48W	Housing Material	Aluminum+Iron
Lumens	600	Lens	Acrylic
Certification (UL/ETL/FCC)	ETL (LED)	Led Type	Zega AC Driverless Engines&Modules